

Middeck/EXPRESS Sub-Rack Payload Processing Flow

(Why we do that crazy thing we do)

Utilization IPT Meeting March 8, 2002



Middeck vs. EXPRESS Flow

- Middeck/EXPRESS Sub-Rack Payloads have become almost synonymous now that ISS has begun to be responsible for the majority of the manifest
- In reality, the terms mean totally different things
 - Middecks are payloads which are located in the Middeck area of the Orbiter
 - EXPRESS Sub-Rack Payloads are items which are located in an EXPRESS Rack within the ISS
- The confusion is created because many of the items destined for an EXPRESS Rack within the ISS are actually launched in the Orbiter Middeck
 - This could be driven by time criticality, or in the case of 8A, simply because there is no MPLM available.
 - The EXPRESS Rack mimics the attach points of the Middeck for just this reason
- All of this means that the terms are being used interchangeably, but this is only being done to confuse you
 - Payloads can, and do every mission, fly in the middeck which are not even part of ISS
 - Payloads can go up in the MPLM for installation into an EXPRESS Rack and never see the middeck
- The majority of the Utilization team will never see a middeck which is not also an EXPRESS Sub-Rack Payload
 - The exception to this being the team supporting middeck late stow



Middeck vs. EXPRESS Flow

- EXPRESS Sub-Rack Payloads are delivered for PTCS testing several months prior to launch depending on the specific mission schedule
 - Sometimes this is early enough to support an MPLM flow, sometimes it is much later
 - In all cases, we don't want to be too close to launch or we won't have enough time to fix significant issues
- Upon completion of PTCS testing, payloads are either installed in the MPLM, or.....
- The payload is returned to the Payload Developer (PD)
 - Huh? Didn't we just test it for flight?
 - How do we know it won't get damaged?
 - What about configuration control and a million other concerns?
- The answer is that the payload was returned so the PD could prepare the payload for launch in the Orbiter middeck, including time critical operations
 - The PD has responsibility for hardware control after being returned by KSC
 - This is no different than before it arrived at KSC the first time
 - Any updates should be documented in the IDP when the payload is returned to KSC
- The payload may physically stay off-line at KSC or be shipped off-site
- The payload is turned back over to KSC for installation into the middeck anywhere from 10 days to 19 hours prior to flight depending on science requirements

